

A standard linear barcode is positioned vertically on the right side of the page. It consists of vertical black bars of varying widths on a white background.

		Subclass	ISSUE CLASSIFICATION
--	--	----------	----------------------

**PATENT NUMBER**

**BEST AVAILABLE COPY**

## **U.S. UTILITY Patent Application**

U.S.A.	O.I.P.E.	Am	PATENT DATE
SCANNED	SIGN	Q.A.	

APPLICATION NO. 09/784975	CONT/PRIOR	CLASS 455	SUBCLASS 456	ART UNIT 2683	EXAMINER Zewdu
------------------------------	------------	--------------	-----------------	------------------	-------------------

## APPLICANTS

Philip Yu  
Edith Stern  
Parry Willner  
David Greene

TITLE

Systems and methods wherein a base device facilitates a determination of a location associated with an occurrence of an event

PTO-2040  
12/99

TERMINAL DISCLAIMER	DRAWINGS			CLAIMS ALLOWED	
	Sheets Drwg.	Figs. Drwg.	Print Fig.	Total Claims	Print Claim for O.G.
<input type="checkbox"/> The term of this patent subsequent to _____ (date) has been disclaimed.				<b>NOTICE OF ALLOWANCE MAILED</b>	
	(Assistant Examiner) _____ (Date)				
<input type="checkbox"/> The term of this patent shall not extend beyond the expiration date of U.S Patent. No. _____				<b>ISSUE FEE</b>	
	(Primary Examiner) _____ (Date)			Amount Due	Date Paid
<input type="checkbox"/> The terminal ____ months of this patent have been disclaimed.				<b>ISSUE BATCH NUMBER</b>	
	(Legal Instruments Examiner) _____ (Date)				

Form PTO-436A

Form PTO-436A  
FILED WITH:  DISK (CRF)  FICHE  CD-ROM

(Rev. 8/99)

FILED WITH:  DISK (CRF)  FICHE  CD-ROM  
(Attached in pocket on right inside flap)